



MULTI-PARAMETER SMART SENSOR ADAPTER

Connect up to three

AquiStar® Smart Sensors

to a single cable to the surface

Measure and Record

- Conductivity
- pH
- Redox
- Temperature
- TDS
- Level
- Pressure
- Nitrate
- Bromide
- Chloride

Features

ADAPTER FEATURES

- 1.75" (4.4 cm) diameter
- Durable Delrin® material
- Rugged strain relief at cable connection

SMART SENSOR FEATURES

- Low power - 2 internal AA batteries
- External power 12 VDC power option with internal batteries as backup
- 316 SS, Viton®, Teflon® construction (titanium optional)
- Modbus® or SDI-12 interface for greater flexibility
- Up to 520,000 records - depending on sensor
- Non-volatile memory
- Flexible, multi-phase logging sequences
- Pause logging feature
- Delayed start feature
- Wireless connectivity - radios and/or cellular
- Free, easy-to-use software
 - Real time viewing
 - Batch start and data upload capability
 - Table or graph viewing formats for recorded data
 - Easy export to spreadsheets



Closeup



Maximum length: 20 inches (51 cm)

1.75"
4.4cm

Instrumentation Northwest, Inc.



Sales and Service Locations

8902 122nd Avenue NE, Kirkland • Washington 98033 USA
(425) 822-4434 • (425) 822-8384 FAX • info@inwusa.com
4620 Northgate Boulevard, Suite 170 • Sacramento, California 95834
(916) 922-2900 • (916) 648-7766 FAX • inwsw@inwusa.com

©2010 Instrumentation Northwest, Inc. All rights reserved. INW and AquiStar are registered trademarks of Instrumentation Northwest. Delrin, Teflon, and Viton are registered trademarks of DuPont Company. Modbus is a registered trademark of Schneider Electric. Doc # 6D0100r1 - 06/10

1-800-776-9355
<http://www.inwusa.com>